

FWM-1LGX Wall Box with 1 LGX Slot

V.3.0



1 x LGX Slot
Various adaptor plates
available, see overleaf

Description

With the ability to use a full array of adapter types this enclosure offers a flexible solution to the end user, enabling them to incorporate a multi functional enclosure that allows easy access during installation or re-work with no disturbance of the existing cable or fibres.

In the addition to the array of adaptors the enclosure also offers multiple cable entry solutions, fibre cable can be spliced or pre terminated solutions, making this enclosure one of the most flexible on the market.

Features/Benefits

- ▶ Up to 1 LGX components
- ▶ Wall mountable
- ▶ Multiple adapter options available
- ▶ Splicing option available
- ▶ Multiple fixing points
- ▶ Hinged door
- ▶ Accepts loose tube and distribution cable
- ▶ ROHS, REACH SvHC

Applications

- ▶ Data centres, premise installations, telecommunication networks
- ▶ Ethernet, Fibre Channel, ATM, LAN, MAN and WAN
- ▶ Data communication and telecommunication networks
- ▶ Indoor applications

Technical Specification

1 Slot Wall Box	
Height	16cm
Width	13.97cm
Depth	3.98Cm
Net weight	24 kgs
Packaged weight	24.9 kgs
Packaged dimensions	42cm W x 42cmm H X 35cm D
Suitable for Adaptor type	LGX / MTP Cassettes
Number of module positions	1
Material	Cold- rolled steel
Material thickness	16 Gauge
Material finish	Powder coating
Colour	RAL 9004
Operating temperature	-40°c to +50°c
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754,EN297-1
Compliant to	RoHS, Reach/SVHC

Ordering Information

DESCRIPTION	PART NO.
AM Style Wall Box	FWM-1LGX

For a full range of LGX style connector modules, see overleaf